

SENNEBOGEN LLC Equipment Dealer Price List | North America Edition 2024-01 | Valid from Jan 01, 2024 until Dec 31, 2024

Standard Machine Configuration		List Price US\$
► SENNEBOGEN 818 M "E" series	\$	477,870
Engine	Ψ	477,070
 Cummins B4.5 diesel engine (4 cylinder) with direct injection, water cooled (TIER 4f emission) 		
 Engine output 154 HP (115 kW) @ 2,200 rpm 		
 Turbo Intercooler & water cooler hydraulically driven, reversible 		
 Automatic idle-stop control and eco-mode for diesel engine 		
Hydraulic System		
 Computer free, state-of-the-art load-sensing with flow-on-demand control 		
 Hydraulic cooler hydraulically driven, reversible 		
 Hydro-Clean filtration system with water absorption and contamination indicator 		
Upper Carriage & Swing System		
 Torsion free, precisely machined upper carriage frame 		
 High torque axial piston swing motor 		
 Large dimensioned, internal teeth swing bearing 		
 Automatic central lubrication system for upper carriage and swing bearing 		
► Handrail on top of upper carriage		
► Fire extinguisher set (1x cab, 1x storage compartment) - brackets installed, extinguisher shipped separate to dealer		
► Light Package consisting of: 2x halogen in cab roof, 2x in frame		
Operator's Cab "maXCab"		
 Hydraulic elevating cab system "E270" (elevation: 8'8") 		
► Catwalk with handrail beside cab		
"maXCab" with sliding door and door window as sliding window, sunshade, floor mat		
Skylight of bullet proof glass		
Windshield of bullet proof glass (fixed / no tilt out)		
► Front & top cab protection guard		
 Automatic climate control with AC, heater and defroster 		
AM/FM radio with MP3/Bluetooth		
 SENCON visual and acoustic diagnostic system for monitoring all essential machine functions 		
Air suspended and adjustable operator's seat incl. armrests, seat heater, headrest, seat belt		
 Camera system with display in cab 		
► LED light package on cab, rear		
Strobe light mounted on cab		
 Operator's & Maintenance manual incl. hydraulic & electric schematics (1x print / 1x digital) 		
Spare Parts catalogue (1x print / 1x digital)		
Working Equipment		
K10 - reach 32'9" / purpose built material handling working equipment (incl. addit. HD counterweight)		
straight material handling boom 20' 4", with end stop monitoring system and limit switches		
straight material handling stick 13' 9", with end stop monitoring system and limit switches		
Boom & Stick cylinders equipped with safety check valves and end position dumping		
Additional Light Package consisting of: 1x at boom, 2x at stick		
Attachment open/close and rotate hydraulic circuits and lines installed up to the end of the stick (ball valves)		
 Rubber tired under carriage MP21E with 4-point outriggers Automatic under carriage interview is a second seco		
Automatic unlock of oscillating axle if upper carriage in longitudinal direction to under carriage		
 Solid rubber tires 10.00-20 (8 units) inclusive intermediate protection ring Standard and the standard standard		
Steering via joy stick, front wheel steering All wheel drive via variable budgevia meter with 2 steere shift transmission		
 All wheel drive via variable hydraulic motor with 2-stage shift transmission Distantian guard for under corriges to protect transmission, hydraulic motor and drive shefts. 		
 Protection guard for under carriage to protect transmission, hydraulic motor and drive shafts a circuit some brake system with additional cafety brake 		
 2-circuit servo brake system with additional safety brake Centralized lubrication points (front & rear) for lubrication of under carriage components 		
 Audible travel alarm while driving machine (forward & backward) 		
 Tool box w/ basic tools, stick pin, grease gun, wheel chock, green & gray touch up paint located in under carriage tool box 		
Magnet System		
 ► 10 kW magnet system, hydraulic driven 	\$	26,930
 Plug in front of stick to hook up magnet, magnet connection cable in under carriage tool box 	φ	20,330
They in mark a build to hook up magnet, magnet connection duble in under carriage tool box		
DEALER LIST PRICE (ex east coast port or storage location)	\$	504,800
Delivery Surcharge:		
shipments gulf coast port, e.g. Galveston, TX or Veracruz, Mexico (dealer net)	\$	3,180
shipments west coast port, e.g. Port Hueneme, CA or Tacoma, WA (dealer net)	\$	6,460



SENNEBOGEN LLC Equipment Dealer Price List | North America Edition 2024-01 | Valid from Jan 01, 2024 until Dec 31, 2024

Optional Machine Equipment (**Option shown is only available as a new factory installation - US retrofit is not possible) Magnet Suspensions (ex Stanley, NC)			
Magnet suspension link inclusive shackle	\$	4,6	
Orange Peel Grapples (terms see attachment price list)	÷	1,0	
 SENNEBOGEN orange peel grapple, 0.50 yd3, 4 tine, semi-closed, OP4-050SEN-S-RT502 (incl. hanger & hoses) 	\$	48,5	
 SENNEBOGEN orange peel grapple, 0.75 yd3, 4 tine, semi-closed, OP4-075SEN-S-RT502 (incl. hanger & hoses) 	\$	50,3	
 SENNEBOGEN orange peel grapple, 0.52 yd3, 5 tine, semi-closed, OP5-040SEN-S-RT502 (incl. hanger & hoses) 	\$	54,7	
Hydraulic System	Ψ	04,7	
 **Additional bar saw slasher hydraulic w/ connections at the under carriage (ball valves) 		on requ	
Live and Dead Heels (for logging applications)		onrequ	
 **Dead heel HD-25SEN kit in combination with ULS (incl. heel, pins), dealer installation 	\$	7,1	
 **Live heel HWG-25SEN-3 kit in combination with ULS (incl. cylinder, heel, hoses excl. hydraulics), dealer installation 	\$	36,0	
Engine	φ	30,0	
	\$	2.6	
Electric refueling pump with level shut-off the state of the		2,5	
► **Cummins QSB4.5 diesel engine (4 cylinder) with direct injection, water cooled (TIER 3 emission) not valid for USA	deduct \$	(28,9	
Hydraulic System			
► Bio degradable hydraulic oil instead of standard hydraulic oil (PANOLIN HLP Synth 46)	\$	8,	
**Live heel hydraulic including hydraulic, controls and hoses to boom head	\$	12,9	
Operator's Cab "maXCab"	•		
**Fixed cab elevation system "E150" (Box style - elevation: 4'11") Hydraulically tilting for transport / incl. catwalk beside cab	\$	12,4	
**Fixed cab elevation system "E200" (Box style - elevation: 6'6") Hydraulically tilting for transport / incl. catwalk beside cab	\$	20,3	
 Right, left and door window of shatter-proof lexan (polycarbonate) 	\$	3,6	
Windshield Wiper for lower glass	\$	1,5	
Additional Camera; please define location (in addition to existing cameras, maximum of 4 total possible)	\$	1,1	
French operator's manual, maintenance manual & spare parts catalogue (1x print / 1x digital)	\$	1,1	
Spanish operator's manual, maintenance manual & spare parts catalogue (1x print / 1x digital)	\$	1,1	
Working Equipment			
K9 - straight boom / straight stick (ball valves)	deduct \$	(6,4	
**B8 ULM - Bended boom / straight stick incl. cylinder, linkage and hydraulics (ball valves)	\$	12,1	
**K9 ULM - straight boom / straight stick incl. cylinder, linkage and hydraulics (ball valves)	\$	11,2	
**K10 ULM - straight boom / straight stick incl. cylinder, linkage and hydraulics (ball valves)	\$	11,2	
**K9 ULS - straight boom / straight universal logging stick (for heel applications, for live heel please add hydraulics & heel)	\$	6,8	
▶ **Boom floating device (recommended for barge unloading - note: the boom will raise when the grapple closes)	\$	4,6	
Under Carriage			
Pneumatic tires 10.00-20 (8 units)	deduct \$	(4,	
► Pneumatic tires 650/50-22.5 (4 units)	\$	16,9	
► Bent 4-point outriggers for increased ground clearance (attention: wider transport width)	\$	12,4	
**Steering via steering wheel (instead of joystick steering)	deduct \$	(
Individual control of 4-point outriggers	\$	8,7	
 **Blade in addition to 4-point outriggers (over front), only in combination with individual outrigger control 	\$	22,	
Low Temperature	<u> </u>	,	
Low temperature package consisting of:	\$	11,	
> electric pre-heating engine block	Ŧ	,	
> electric pre-heating hydraulic tank			
> electric pre-heating water separator			
> one plug 110 V outside of machine			